# Simulateur de portée - 800 Mouvements si



## - Configurable range simulator - Simultaneous arming of 800 watch heads

## Faithful reproduction of the automatic winding of the watch movement

- + Programming cycles
- + 2 independant stations
- + Loading from 1 to 800 watch heads
- + Multiple settings
  - Speed
  - Position (number of revolutions)
  - Acceleration
  - Deceleration





AGING PROCESS

Special machinery

Inspection equipment

Watchmakers tools

### **GYROLAB**

### **RANGE SIMULATOR**



Device for faithfully simulating the arming of a watch movement based on the rotation of 2 axes in simultaneous motion.

#### **SPECIFICATIONS**

- + Max. load per station: 30 Kg
- + Loading capacity: 12 trays\*
- + Angular orientation: 360° (double axial rotation)
- + Rotation Speed: 3 à 100 revs.min-1
- \* may vary depending on customer specifications



Simple loading structure adaptable to all types of packaging

- **2 independent, programmable stations** with Servo Spin software:
- + Position control
- + Speed control
- + Acceleration and deceleration control
- + Communication via web browser without software installation (PC, MAC, Linux compatible)



Servo Spin Software: user-friendly and flexible cycle creation

**On-board intelligence** guarantees independent operation and eliminates any disruption caused by PC updates or shutdowns.



